



Call AESI for additional details: (866) 736-AESI (2374)

LCD Model	KT-LS15XH	KT-LS17E6	KT-LS19E1
Size	15.0"	17.0"	19.0"
Pixel Pitch	0.297mm*0.297mm	0.264mm*0.264mm	0.294mm*0.294mm
Display Color	16.7M	16.2M	16.7M
Contrast Ratio	300 : 1	500 : 1	600 : 1
Brightness	250cd/m2	250cd/m2	250cd/m2
View Angle (U/D/L/R)	70/70/60/65	85/85/85/85	85/85/85/85
Interface	LVDS	LVDS	LVDS
Resolution	1024*768	1280*1024	1280*1024
OSD Control	Auto, Contrast, Brightness, H/V Position H-Size Phase, Auto-Level, Color Control, Text/Move OSD Position, OSD Time-Out, Power Save Delay Language, Information	Auto, Contrast, Brightness, H/V Position H-Size Phase, Auto-Level, Color Control, Text/Move OSD Position, OSD Time-Out, Power Save Delay Language, Information	Auto, Contrast, Brightness, H/V Position H-Size Phase, Auto-Level, Color Control, Text/Move OSD Position, OSD Time-Out, Power Save Delay Language, Information
Input Signal	Analog R/G/B	Analog R/G/B	Analog R/G/B
Power Adapter	Input : AC100V-240V, 50Hz-60Hz Output : 12VDC (Option: Combo board)	Input : AC100V-240V, 50Hz-60Hz Output : 12VDC (Option: Combo board)	Input : AC100V-240V, 50Hz-60Hz Output : 12VDC (Option: Combo board)
Safety	UL/CE/CB/FCC/TUV	UL/CE/CB/FCC/TUV	UL/CE/CB/FCC/TUV